


BSM



Masonry

Fireclay (chamotte)

Diamond core bit for dry use · brazed · high-performance roof-top segments



DIAMETER

Ø 52–300 mm

OPERATING MODE

Dry

BORE

1¼", GK, (3-hole)

SUITABLE FOR



Core drilling machine
from 1.6 kW

Versions

BSM

- for fireclay bricks, fireclay pipes & masonry
- short version for freehand drilling
- for machines with dust extraction

Ø	SIZE
52	24×3.5×9
57	24×3.5×9
62	24×3.5×9
67	24×3.5×9
72	24×3.5×9
82	24×3.5×9
87	24×3.5×9
92	24×3.5×9

Ø	SIZE
102	24×3.5×9
107	24×3.5×9
112	24×3.5×9
122	24×3.5×9
127	24×3.5×9
132	24×3.5×9
138	24×3.5×9
142	24×4.0×9
152	24×4.0×9
162	24×4.0×9
172	24×4.0×9
182	24×4.0×9
192	24×4.0×9
202	24×4.0×9
212	24×4.0×9
225	24×4.0×9
232	24×4.5×9
250	24×4.5×9
272	24×4.5×9
300	24×4.5×9

- Peripheral speed: approx. 3 m/s.
- Standard working length: 250 mm / 350 mm
- Application: for electrically driven motors
- Other working lengths on request

Enquiries and orders

Customers can find technical data sheets in the customer area at vena-d.de.

+49 2737 914 84
info@vena-d.de