

NLU-ASPHALT

Asphalt



EN 13236

Brazed diamond joint cutter · cutting widths from 5 mm to 20 mm



DIAMETER

Ø 300–500 mm

OPERATING MODE

Dry or wet

BORE

25.4 / 30 / 35 mm

QUALITY LEVEL



Entry FEC-ASPHALT >

NLU-ASPHALT

Premium

SUITABLE FOR



Floor saw
up to 35 kW

Versions

NLU-ASPHALT

- with reinforced core & core protection
- excellent tool life
- High Performance – powerful

Ø	SEGMENTS	SIZE
300	21+3	40×5.0x10
300	21+3	40×6.0x10
300	21+3	40×8.0x10
300	21+3	20×10.0x10
300	21+3	20×20.0x10
350	35+3	40×5.0x10

Ø	SEGMENTS	SIZE
350	35+3	40×6.0x10
350	35+3	40×8.0x10
350	35+3	20×10.0x10
350	35+3	20×20.0x10
400	40+4	40×5.0x10
400	40+4	40×6.0x10
400	40+4	40×8.0x10
400	40+4	20×10.0x10
400	40+4	20×20.0x10
450	44+4	40×5.0x10
450	44+4	40×6.0x10
450	44+4	40×8.0x10
450	44+4	20×10.0x10
450	44+4	20×20.0x10
500	50+5	40×5.0x10
500	50+5	40×8.0x10
500	50+5	20×10.0x10
500	50+5	20×20.0x10

- Peripheral speed: 80 m/s.
- We can make drive pin holes to suit your machine on request.

Enquiries and orders

Customers can find technical data sheets in the customer area at vena-d.de.

+49 2737 914 84
info@vena-d.de