

PERFORCER SX



Reinforced concrete

Diamond core bit for fast drilling · brazed



DIAMETER

Ø 10–45 mm

OPERATING MODE

Wet

BORE

**R½", from Ø25 mm
also with 1¼"**

SUITABLE FOR



Core drilling machine
from 1.6 kW

Versions

PERFORCER SX

- Roof-top rings for easy starting
- High Performance, reinforced concrete

Ø	SEGMENTS	SIZE
10	Ring	10×2.5
12	Ring	12×2.5
14	Ring	14×2.5
16	Ring	16×2.5
18	Ring	18×2.5
20	Ring	20×2.5
22	Ring	22×2.5
24	Ring	24×2.5

Ø	SEGMENTS	SIZE
25	Ring	25×2.5
26	Ring	26×2.5
28	Ring	28×2.5
30	Ring	30×2.5
32	Ring	32×2.5
35	Ring	35×2.5
38	Ring	38×2.5
40	Ring	40×2.5
42	Ring	42×2.5
45	Ring	45×2.5
36	4	17×3.0x7
38	4	17×3.0x7
40	4	17×3.0x7
42	5	17×3.0x7
45	5	17×3.0x7

- Peripheral speed: approx. 3 m/s.
- Standard working length: 320 & 400 mm
- Application: for electrically driven drill motors.

Enquiries and orders

Customers can find technical data sheets in the customer area at vena-d.de.

+49 2737 914 84
info@vena-d.de