


ROTO-CUT

Concrete (universal)



EN 13236

Laser-welded diamond saw blade · 10 mm segment height



DIAMETER

Ø 115–600 mm

OPERATING MODE

Dry or wet

BORE

22.2 mm · 20 / 25.4 /
30 mm · M14

QUALITY LEVEL



SUITABLE FOR



Angle grinder



Cut-off saw



Table saw



Floor saw



Site saw

Versions

ROTO-CUT

- Good value for money

Ø	SEGMENTS	SIZE	BORE
115	9	40×2.2×10	22.2 mm
125	10	40×2.2×10	22.2 mm
150	12	40×2.2×10	22.2 mm
180	14	40×2.2×10	22.2 mm
230	16	40×2.4×10	22.2 mm

Ø	SEGMENTS	SIZE	BORE
300	20	40×3.0×10	20 / 25.4 / 30 mm
350	24	40×3.2×10	20 / 25.4 / 30 mm
400	28	40×3.2×10	20 / 25.4 / 30 mm
450	31	40×3.6×10	20 / 25.4 / 30 mm
500	35	40×3.6×10	20 / 25.4 / 30 mm
600	42	40×4.2×10	20 / 25.4 / 30 mm

ROTO-CUT with M14 threaded flange

Ø	SEGMENTS	SIZE	BORE
115	9	40×2.2×10	M14
125	10	40×2.2×10	M14
150	12	40×2.2×10	M14
180	14	40×2.2×10	M14
230	16	40×2.4×10	M14

- Peripheral speed: 100 m/s.
- Suitable accessories: [Mounting flanges](#)

Enquiries and orders

Customers can find technical data sheets in the customer area at vena-d.de.

+49 2737 914 84
info@vena-d.de